

# Safety Data Sheet

## SDS 123 -- Carbon Graphite with Barium Treatment

### 1. Product and Company Information

Product Name	Carbon Graphite with Barium Treatment
MSDS Number	123
Recommended Product Use	Solid electrical blocks and brushes
Restrictions on Product Use	None
Manufacturer	Helwig Carbon Products, Inc. 8900 W. Tower Ave. Milwaukee, WI 53224  info@helwigcarbon.com
Print Date	8/17/2017 12:39
Emergency Phone number	1-414-354-2411 1-800-962-4851

### 2. Hazards Identification

This material is not considered hazardous in its solid form , but may create hazardous dust during shipping, handling and use.

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)      Skin corrosion (Category 1B), H314  
Serious eye damage (Category 1), H318

GHS Label Elements

Pictogram



Signal Word      Warning

Hazard Statements

H319      Causes serious eye irritation.  
H335      May cause respiratory irritation.

Precautionary Statements

P264      Wash skin thoroughly after handling.  
P280      Wear protective gloves/ protective clothing/ eye protection/ face protection.

P305+P351+P338      IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313      If eye irritation persists: Get medical advice/ attention.

P261	Avoid breathing dust
P271	Use only outdoors or in a well-ventilated area.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or a doctor/physician if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.
Hazards not otherwise classified	Dust generated during shipping, handling, or use may form combustible dust concentrations in air. Prevent dust accumulations. The dust is electrically conductive and dust accumulations on electrical equipment can cause short circuits. Dust from this product contains graphite and may create slippery conditions. Maintain good housekeeping.

### 3. Composition/Information on ingredients

Ingredient Name	CAS number	Concentration % (w/w)	Classification
Graphite	7782-42-5	0-95%	H319 -- Eye Irrit. 2 H335 -- STOT SE 3 -- Resp Tract
Carbon	7440-44-0	0-90%	
Barium Hydroxide	12230-71-6	0-2%	H302+H332 -- Harm. If swallowed or inhaled H314 -- Causes severe skin burns and eye damage

### 4. First Aid Measures

<b>General</b>	First aid may be required if exposed to large quantities of dust generated from material. Never give anything by mouth to an unconscious person. If exposed or concerned: Get medical advice/attention.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
<b>Skin contact</b>	Remove contaminated clothing. Wash with soap and water. Wash contaminated clothing before reuse.
<b>Inhalation</b>	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. When symptoms occur: go into open air and ventilate suspected area
<b>Ingestion</b>	Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
<b>Protection of first aid personnel</b>	No action shall be taken involving any personal risk or without suitable training. If it is suspected that dust is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus.

### 5. Fire-fighting measures

### Extinguishing media

**Suitable**

Use suitable extinguisher for surrounding fire.

**Not suitable**

Do not use water jet when dust is present

**Special exposure hazards**

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Hazardous combustion products**

Combustion products may include the following materials: carbon monoxide, carbon dioxide.

**Special protective equipment for fire-fighters**

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**Special Remarks on Hazards**

Graphite dusts with particles sizes from 4 to 40 µm are able to explode in a wide range of concentrations. The minimum ignition energy is 1kJ for the finest dust. The dusts tested were ranked as St.1 class. Denkevits, A. (2003)

## 6. Accidental release measures

Minimize airborne dust and eliminate all sources of fire/ignition. Do not use air hoses for cleaning. Minimize dry sweeping to avoid generation of dust clouds. Vacuum dust accumulations. Vacuums with explosion proof motor should be used.

### Personal precautions, protective equipment and emergency procedures

**Personal precautions**

No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid generating dust clouds. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**Environmental precautions**

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

**Large spill**

Move containers from spill area. Avoid creating dusty conditions or wind dispersal. Vacuum or sweep material into labeled waste containers. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

**Small spill**

Move containers from spill area. Vacuum or sweep material into labeled waste containers. Dispose of via a licensed waste disposal contractor.

## 7. Handling and storage

### Precautions for safe handling

**Advice on general occupational hygiene**

Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. Dust levels must be kept within prescribed limits. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Protective measures**

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Non-sparking tools should be used when working with dust.

**Conditions for safe storage, including any incompatibilities**

Store solid block material in a safe manner. Store any dust generated in a closed container.

**8. Exposure controls/personal protection**

Component	CAS number	Value	Control parameters	Basis
Graphite	7782-42-5	8 hr TWA	15 mg/m <sup>3</sup> total dust 5 mg/m <sup>3</sup> respirable fraction	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		8 hr TWA TLV	2 mg/m <sup>3</sup> respirable	ACGIH® 2015
Carbon	7440-44-0	8 hr TWA	15 mg/m <sup>3</sup> total dust 5 mg/m <sup>3</sup> respirable fraction	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		8 hr TWA TLV	2 mg/m <sup>3</sup>	ACGIH® 2015
Barium Hydroxide	12230-71-6	8 hr TWA	0.5 mg/m <sup>3</sup>	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		8 hr TWA TLV	0.5 mg/m <sup>3</sup>	ACGIH® 2015

**Consult local authorities for acceptable exposure limits.**

**Recommended monitoring procedures**

This product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

**Engineering measures Engineering measures**

It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling dusts generated from this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

**Hygiene measures**

Wash hands, forearms and face thoroughly after handling product, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

**Respiratory**

Use NIOSH-approved respiratory protective equipment if exposures exceed established limits.

**Hands**

Wear gloves appropriate for task being performed.

**Eyes**

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary. Safety glasses with side shields recommended.

**Skin**

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Environmental exposure controls**

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

<b>9. Physical and chemical properties</b>
--

<b>Form</b>	Solid
<b>Appearance</b>	Gray to Black Solid
<b>Odor</b>	None
<b>Odor threshold</b>	No data available
<b>pH</b>	Barium Hydroxide: 12.5 @ 50g/l at 20°C
<b>Melting point</b>	Not Applicable
<b>Boiling point</b>	3650°C (6602°F) sublimes
<b>Flask Point</b>	No data available
<b>Evaporation rate</b>	No data available
<b>Flammable limits</b>	
<b>Lower:</b>	Not Applicable
<b>Upper:</b>	Not Applicable
<b>Vapor pressure</b>	No data available
<b>Vapor density</b>	Not Applicable
<b>Relative density</b>	1.2-2.2 g/cm <sup>3</sup>
<b>Solubility</b>	Barium Hydroxide soluble in water
<b>Partition coefficient: n-octanol/water</b>	No data available
<b>Partition coefficient</b>	
<b>Auto-ignition temperature</b>	No data available
<b>Decomposition Temperature</b>	3650°C (6602°F) sublimes
<b>Viscosity</b>	Not Applicable

## 10. Stability and reactivity

<b>Stability</b>	The product is stable. Under normal conditions of storage and use, hazardous polymerization will not occur.
<b>Conditions to avoid</b>	Minimize airborne dust generation
<b>Materials to avoid</b>	Reactive or incompatible with the following materials: oxidizing materials
<b>Hazardous decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 11. Toxicological information

<b>Acute toxicity:</b>	<u>Barium Hydroxide: LD50 Oral - rat 550 mg/kg</u>
<b>Skin Corrosion/Irritation:</b>	No data available
<b>Serious Eye Damage/Irritation:</b>	No data available
<b>Respiratory or Skin Sensitization:</b>	No data available
<b>Germ Cell Mutagenicity:</b>	No data available
<b>Teratogenicity:</b>	No data available
<b>Carcinogenicity:</b>	No data available
<b>Specific Target Organ Toxicity (Repeated Exposure):</b>	No data available
<b>Reproductive Toxicity:</b>	No data available
<b>Specific Target Organ Toxicity (Single Exposure):</b>	No data available
<b>Aspiration Hazard:</b>	No data available
<b>Potential Adverse Human Health Effects and Symptoms:</b>	No known significant effects or critical hazards.
<b>Symptoms/Injuries After Inhalation:</b>	No known significant effects or critical hazards.
<b>Symptoms/Injuries After Skin Contact:</b>	No known significant effects or critical hazards.
<b>Symptoms/Injuries After Eye Contact:</b>	No known significant effects or critical hazards.
<b>Symptoms/Injuries After Ingestion:</b>	No known significant effects or critical hazards.
<b>Chronic Symptoms:</b>	No known significant effects or critical hazards.

## 12. Ecological information

<b>Environmental effects</b>	
<b>Toxicity:</b>	No data available
<b>Persistence and degradability</b>	No data available
<b>Bioaccumulative Potential</b>	No data available
<b>Mobility in soil</b>	
<b>Soil/water partition coefficient</b>	No data available
<b>Other adverse affects</b>	The material is inert and is not expected to pose a threat to the environment.

## 13. Disposal considerations

**Waste disposal**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**14. Transport information**

## 14.1 In Accordance with DOT

Identification Number : not regulated  
Hazard Class :  
Packing Group :  
Proper Shipping Name :  
Label Codes :  
ERG Number :

## 14.2 In Accordance with IMDG

Identification Number : not regulated  
Hazard Class :  
Packing Group :  
Label Codes :  
Proper Shipping Name :

## 14.3 In Accordance with IATA

Identification Number : not regulated  
Hazard Class :  
Packing Group :  
Proper Shipping Name :  
Label Codes :  
ERG Code (IATA) :

**15. Regulatory information****SARA 302 Extremely Hazardous Substances**

Not Listed

**SARA 311/312 Classification**

Barium hydroxide ( CAS 12230-70-6 )

**SARA 313 - Supplier Notification**

Barium hydroxide ( CAS 12230-70-6 )

**Massachusetts Right To Know Components**

Not Listed

**Pennsylvania Right To Know Components**

Barium hydroxide ( CAS 12230-70-6 )

**New Jersey Right To Know Components**

Barium hydroxide ( CAS 12230-70-6 )

**California Prop. 65 Components**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**16. Other information**

Full Text of H phrases  
in section 2 & 3

STOT	Specific target organ toxicity
Eye Irrit.	Eye irritation
Resp Tract	Respiratory tract

Hazardous Material Information  
System III (U.S.A.)

Health : 1  
Flammability: 0  
Physical hazards : 0  
Chronic :

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

The customer is responsible for determining the PPE code for this material.

NFPA Rating

Health hazard: 1  
Fire Hazard: 0  
Reactivity Hazard: 0

Prepared By	Helwig Carbon Products, Inc.
Date of Issue	1-Mar-2015
Date of Printing	17-Aug-2017
Version	1.1

**Notice to Reader**

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.