
PREMIER MOUNTING VERSATILITY FOR HELWIG BPKs™



helwigcarbon.com/shaft-grounding/multifit-brackets

BRACKETS COVER SHAFT SIZES RANGING FROM 0.5" - 6"
MOUNTS USING EXISTING RETAINING BOLTS



### ■ IDEAL MOUNTING ACCESSORY FOR MOTOR SHOPS & FIELD INSTALLS

### IN STOCK & READY TO SHIP




### **KEY ADVANTAGES**

- MultiFit Brackets provide a solid and adjustable base for mounting a Helwig BPK<sup>™</sup> without drilling and tapping
- These brackets were designed with versatility in mind, catering to field installs, motor shops and harsh environments
- Use our online MULTIFIT BRACKET SELECTION TOOL to determine the best solution for your application

# BPK FIELD PACK

All-in-one shaft grounding variety pack that combines the superior protection of Helwig's Bearing Protection Kits and the versatility of MultiFit Brackets.



## **BPK-FIELD PACK**

- (4) EZ-1 MultiFit Brackets & hardware
- (4) EZ-3 MultiFit Brackets & hardware
- Recessed Bolt Adapters

Non-Bracket Mounting Option



### \*mounting hardware not pictured 🔲 IDEAL FOR MOTOR SHOPS & FIELD INSTALL 🔲 IN STOCK & READY TO SHIP



### CUSTOM MOUNTING BRACKETS

- For large quantities, we can develop custom brackets for a tailored solution
- Motor OEMs like WEG, Teco Westinghouse, NAE, and World Wide Electric have partnered with Helwig to design multiple custom brackets for their specific motor frames

### **BPK<sup>™</sup> Selection Guide**

Shaft Diameter	0.0" 0mm		L.5" 3mm	2.0 50m		3.0 75 n	8.5" 9mm	4.0 101n		5.0 127r	5.5" Omm	6. 152	
BPK-IM2													
BPK-IM5													
BPK-4/S/SB													
ВРК-АМ													

Adjust kit until perpendicular to shaft, use the red retaining clip to set shaft-to-BPK distance

- Ensure the shaft has a surface finish between 8 and 63 RMS (standard motor shaft finish)
- For shaft diameters larger than 6.0" (152mm) or for high vibration/extremely rough applications please contact Helwig for assistance: (800) 962-4851 or carboncrew@helwigcarbon.com